USB Crash Cart Adapter with File Transfer & Video Capture - TAA

Product ID: NOTECONS02



The USB crash cart adapter gives you control of a headless system, turning your laptop into a portable crash cart for rack servers, PCs, ATMs, kiosks, and more.

Simply connect the laptop crash cart adapter to your computer using the included USB cable, then connect the integrated USB and VGA cables to your server for instant BIOS-level control. With no server-side software required, you can be up and running instantly.

*Please note that the mouse function may be limited in some BIOS/UEFI environments

With the flexible software interface, you can transfer files from your laptop to the server, capture videos for records or instructional purposes, take screenshots and scale the display window to full screen mode or smaller, with no scroll bars helping you to troubleshoot faster.

Powered from the server-side USB connection, the KVM adapter doesn't require an AC outlet so you can connect to any PC or device that has a VGA and USB port, even if there's no power outlet available.

This pocket-sized adapter features a compact design that easily fits inside your laptop bag and requires no additional accessories to connect, eliminating the need to lug around a large, awkward traditional crash cart to troubleshoot and service your systems.

StarTech.com offers a wide selection of high-quality KVM-related products to help you access your systems more efficiently without the expense and clutter of extra keyboards, mice and monitors.

Certifications, Reports and Compatibility



Applications

• ATM and VLT maintenance and repair

• Mobile systems and server repair

Features

• BUILT FOR SERVERS & LEGACY SYSTEMS: Ideal for servers and industrial PCs with native VGA video; USB Crash cart adapter connects your laptop to a legacy headless system, turning your laptop into a portable console for servers, PCs, ATMs, kiosks, etc

• EFFICIENT TROUBLESHOOTING: Transfer files, take screenshots, log activity using the downloadable software (pen drive not incl); Download & install the latest drivers & software for the specific NOTECONS02X model (see additional content for more info)

• BIOS-LEVEL CONTROL: Connect the crash cart adapter to your laptop using the included USB cable, then connect the integrated USB & VGA cables to your server for instant BIOS-level control; Note: Mouse function may be limited in some BIOS/UEFI environments

• SELF-POWERED: The KVM adapter is powered by the server-side USB connection, reducing strain on the laptop's battery and eliminating the need for an AC outlet, allowing you to connect to any PC or device with a VGA output port and USB connection

• COMPACT DESIGN: This TAA Compliant pocket-sized data center crash cart adapter requires no additional accessories, eliminating the need to carry around a traditional crash cart/trolley when troubleshooting and servicing your systems

General		
	UPC	065030854382
	Package Quantity	1
	Warranty	2 Years

Special Notes / Requirements		
	Special Notes	Windows Legacy and Support Note(s): Windows XP, Vista; Windows Server 2008 R2 Linux Support Note(s): Linux 2.6 and up (LTS Versions only) - If you're interfacing with a Linux device, this adapter is only compatible with standard QWERTY keyboards in U.S English configuration - Note: Mouse function may be limited or non-functional in some BIOS/UEFI environments
Power		
	Power Source	USB-Powered
Physical & Environmental		
	Color	Black
	Material	Plastic
	Cable Length	16.4 in [41.6 cm]
	Product Length	5.2 in [13.3 cm]
	Product Width	2.9 in [74.0 mm]
	Product Height	0.6 in [15.0 mm]
	Product Depth	4.5 in [11.5 cm]
	Weight of Product	6.0 oz [170.0 g]
	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-40C to 70C (-40F to 158F)
	Humidity	80% RH
Performance		
	IP Control	No
	Hot-Key Selection	No
	On-Screen Display	No
	Maximum Number of Users	1

	MTBF	909000
	Maximum Analog Resolutions	1920x1200 @ 60Hz

Hardware

CAC Support	No
Audio	No
Number of KVM Ports	1
Supported Platforms	USB
PC Video Type	VGA
Number of Monitors Supported	1
Rack-Mountable	No
Cables Included	Yes
Cascadable	No
LED Indicators	1 - User Console/USB Link
	1 - Host/Server Video (VGA) Link
	1 - Host/Server Keyboard/Mouse USB Link

Packaging & In-the-Box

Included in Package	1 - USB Crash Cart Adapter
	1 - USB A to Mini-B Cable
Package Width	11.9 in [30.1 cm]
Package Depth	6.5 in [16.5 cm]
Package Height	2.2 in [55 mm]
Shipping (Package) Weight	12.6 oz [358 g]

Connector(s)

Host Connector 1 (Quantity)	1

Host Connector 1	VGA
Host Connector 2 (Quantity)	1
Host Connector 2	USB-A (480Mbps, 2.5W)
Connector 1 (Quantity)	1
Connector 1	USB Mini-B (480Mbps, 2.5W)

Product appearance and specifications are subject to change without notice.